# O'Keeffe's Aluminum Ladder by SAFTI FIRST

### Health Product Declaration v2.2 created via: HPDC Online Builder

### HPD UNIQUE IDENTIFIER: 28598

CLASSIFICATION: 05 51 00 Metal Stairs

PRODUCT DESCRIPTION: O'Keeffe's manufactures the most specified aluminum ladder in the USA, with the innovative "first in the industry" square serrated rung for maximum grip and foot traction. With a fully integrated manufacturing facility and an extensive aluminum building products line, O'Keeffe's can custom fabricate virtually any type of fixed access, ship, cage or custom ladder you need - offering great design flexibility with a variety of options. O'Keeffe's ladders are built to the highest standards and are made with maintenance-free, lightweight, non-spark, high-strength aluminum construction. Our products are proudly made in the USA for fast lead times and competitive pricing. With over 75 years of design, engineering, and manufacturing experience, our dedicated staff can assist you from concept to completion.

# Section 1: Summary

## CONTENT INVENTORY

- **Inventory Reporting Format**
- Nested Materials Method
- C Basic Method
- Threshold Disclosed Per
- O Material
- O Product

Threshold Level © 100 ppm © 1,000 ppm © Per GHS SDS

C Other

Residuals/Impurities Considered in 2 of 2 Materials

Explanation(s) provided for Residuals/Impurities? © Yes © No

# **Nested Method / Product Threshold**

All Substances Above the T	Threshold Indicated Are: ℃ Yes Ex/SC ⓒ Yes ♡ No			
% weight and role provided Screened	d for all substances. ○ Yes Ex/SC ⊙ Yes ○ No			
All substances screened using Priority Hazard Lists with results disclosed.				
One or more substances no	○ Yes Ex/SC ○ Yes ⊙ No of disclosed by Name			

One or more substances not disclosed by Name (Specific or Generic) and Identifier and/ or one or more Special Condition did not follow guidance.

### CONTENT IN DESCENDING ORDER OF QUANTITY

Summary of product contents and results from screening individual chemical substances against HPD Priority Hazard Lists and the GreenScreen for Safer Chemicals®. The HPD does not assess whether using or handling this product will expose individuals to its chemical substances or any health risk. Refer to Section 2 for further details.

MATERIAL | SUBSTANCE | RESIDUAL OR IMPURITY GREENSCREEN SCORE | HAZARD TYPE

ALUMINUM EXTRUSION [ UNS A96063 ALUMINUM ALLOY NoGS ] STAINLESS STEEL HARDWARE [ UNS S30300 STAINLESS STEEL ALLOY NoGS ] Number of Greenscreen BM-4/BM3 contents ... 0

Contents highest concern GreenScreen Benchmark or List translator Score ... NoGS

Nanomaterial ... No

### INVENTORY AND SCREENING NOTES:

This Health Product Declaration (HPD) was completed in accordance with the HPD Standard version 2.2, and discloses hazards associated with all substances present at or above 100 parts per million (ppm) in the finished product, along with the role and percent weight.

# VOLATILE ORGANIC COMPOUND (VOC) CONTENT

VOC Content data is not applicable for this product category.

**CERTIFICATIONS AND COMPLIANCE** See Section 3 for additional listings.

VOC emissions: Inherently non-emitting source per LEED®

## CONSISTENCY WITH OTHER PROGRAMS

Pre-checked for LEED v4 Material Ingredients Option 1 and Option 2

Third Party Verified?

⊙ No

PREPARER: Self-Prepared VERIFIER: VERIFICATION #: SCREENING DATE: 2022-06-02 PUBLISHED DATE: 2022-06-02 EXPIRY DATE: 2025-06-02 This section lists contents in a product based on specific threshold(s) and reports detailed health information including hazards. This HPD uses the inventory method indicated above, which is one of three possible methods:

- Basic Inventory method with Product-level threshold.
- Nested Material Inventory method with Product-level threshold
- Nested Material Inventory method with individual Material-level thresholds

Definitions and requirements for the three inventory methods and requirements for each data field can be found in the HPD Open Standard version 2.2, available on the HPDC website at: www.hpd-collaborative.org/hpd-2-2-standard

ALUMINUM EXTRUSION	%: 95.0000 - 99.0000			
PRODUCT THRESHOLD: 100 ppm	RESIDUALS AND IMPURITIES	S CONSIDERED: Yes	M	IATERIAL TYPE: Metal
hat have a GS score of BM-1, LT-	TES: No residuals or impurities are expected 1, LT-P1 or NoGS other than those conside nt by weight of material given based on cor	ered "alloying elements"	, as disclosed in t	
UNS A96063 ALUMINUM ALLOY	r			ID: Not registered
HAZARD SCREENING METHOD:	Pharos Chemical and Materials Library	HAZARD SCREENING	DATE: 2022-06	-02 17:42:23
%: 100.0000 - 100.0000	GS: NoGS	RC: Both NANO: No	SUBSTANCE	ROLE: Structure componen
HAZARD TYPE	AGENCY AND LIST TITLES	WARNINGS		
None found				
SUBSTANCE NOTES: Solid extr used for this product consist of materials. In addition to the bas elements that may individually Silicon [7440-21-3]; Max 1.5% M	ruded aluminum provides the structural co f approximately 64% scrap aluminum, inclu se metal, Aluminum [7429-90-5], document exceed the declared threshold: Max 2.5% 2 Manganese [7439-96-5]; Max 1.3% Copper	mponents of the ladder Iding 52% pre-consume ation from supplier prov Zinc [7440-66-6]; Max 2	Supplier has cor r press scrap and rides the following 1% Magnesium [	l 12% post-consumer g composition for alloying 7439-95-4]; Max 1.8%
SUBSTANCE NOTES: Solid extra used for this product consist of materials. In addition to the bas elements that may individually e	f approximately 64% scrap aluminum, incluse metal, Aluminum [7429-90-5], documents exceed the declared threshold: Max 2.5% 2 Manganese [7439-96-5]; Max 1.3% Copper	mponents of the ladder Iding 52% pre-consume ation from supplier prov Zinc [7440-66-6]; Max 2	Supplier has cor r press scrap and rides the following 1% Magnesium [	firmed that aluminum billet 12% post-consumer g composition for alloying 7439-95-4]; Max 1.8%
SUBSTANCE NOTES: Solid extr used for this product consist of materials. In addition to the bas elements that may individually Silicon [7440-21-3]; Max 1.5% M	f approximately 64% scrap aluminum, incluse metal, Aluminum [7429-90-5], documents exceed the declared threshold: Max 2.5% 2 Manganese [7439-96-5]; Max 1.3% Copper	mponents of the ladder Iding 52% pre-consume ation from supplier prov Zinc [7440-66-6]; Max 2	Supplier has cor r press scrap and rides the following 1% Magnesium [	firmed that aluminum billet 12% post-consumer 9 composition for alloying 7439-95-4]; Max 1.8%
SUBSTANCE NOTES: Solid extrused for this product consist of materials. In addition to the base elements that may individually e Silicon [7440-21-3]; Max 1.5% N 47-3]; Max 0.05% Lead [7439-9	f approximately 64% scrap aluminum, incluse metal, Aluminum [7429-90-5], documents exceed the declared threshold: Max 2.5% 2 Manganese [7439-96-5]; Max 1.3% Copper 2-1]. %: 1.0000 - 5.0000	mponents of the ladder iding 52% pre-consume ation from supplier prov Zinc [7440-66-6]; Max 2 [7440-50-8]; Max 1.1%	Supplier has converted by the second	firmed that aluminum bille 12% post-consumer 9 composition for alloying 7439-95-4]; Max 1.8%
SUBSTANCE NOTES: Solid extr used for this product consist of materials. In addition to the bas elements that may individually of Silicon [7440-21-3]; Max 1.5% M 47-3]; Max 0.05% Lead [7439-9 STAINLESS STEEL HARDWARE PRODUCT THRESHOLD: 100 ppm RESIDUALS AND IMPURITIES NOT	f approximately 64% scrap aluminum, incluse metal, Aluminum [7429-90-5], documents exceed the declared threshold: Max 2.5% 2 Manganese [7439-96-5]; Max 1.3% Copper 2-1]. %: 1.0000 - 5.0000	mponents of the ladder uding 52% pre-consume ation from supplier prov Zinc [7440-66-6]; Max 2 [7440-50-8]; Max 1.1%	Supplier has con r press scrap and rides the following 1% Magnesium [ Iron [7439-89-6]; MA	firmed that aluminum biller 12% post-consumer composition for alloying 7439-95-4]; Max 1.8% Max 0.5% Chromium [7440 TERIAL TYPE: Metal Inventory Threshold
SUBSTANCE NOTES: Solid extr used for this product consist of materials. In addition to the bas elements that may individually of Silicon [7440-21-3]; Max 1.5% N 47-3]; Max 0.05% Lead [7439-9 STAINLESS STEEL HARDWARE PRODUCT THRESHOLD: 100 ppm RESIDUALS AND IMPURITIES NOT indicated that have a GS score of Enotes.	f approximately 64% scrap aluminum, incluse metal, Aluminum [7429-90-5], documenta exceed the declared threshold: Max 2.5% 2 Manganese [7439-96-5]; Max 1.3% Copper 12-1]. %: 1.0000 - 5.0000 RESIDUALS AND IMPURITIES TES: No residuals or impurities are expected	mponents of the ladder uding 52% pre-consume ation from supplier prov Zinc [7440-66-6]; Max 2 · [7440-50-8]; Max 1.1%	MA Supplier has con- r press scrap and rides the following 1% Magnesium [ Iron [7439-89-6]; MA bove the Content elements", as disc	firmed that aluminum billed 12% post-consumer g composition for alloying 7439-95-4]; Max 1.8% Max 0.5% Chromium [7440 Max 0.5% Chromium [7440 Inventory Threshold closed in the substance
SUBSTANCE NOTES: Solid extr used for this product consist of materials. In addition to the bas elements that may individually of Silicon [7440-21-3]; Max 1.5% N 47-3]; Max 0.05% Lead [7439-9 STAINLESS STEEL HARDWARE PRODUCT THRESHOLD: 100 ppm RESIDUALS AND IMPURITIES NOT indicated that have a GS score of Enotes.	f approximately 64% scrap aluminum, incluse metal, Aluminum [7429-90-5], documenta exceed the declared threshold: Max 2.5% 2 Manganese [7439-96-5]; Max 1.3% Copper 12-1]. %: 1.0000 - 5.0000 RESIDUALS AND IMPURITIES TES: No residuals or impurities are expected BM-1, LT-1, LT-P1 or NoGS other than those	mponents of the ladder uding 52% pre-consume ation from supplier prov Zinc [7440-66-6]; Max 2 · [7440-50-8]; Max 1.1%	MA Supplier has con- r press scrap and rides the following 1% Magnesium [ Iron [7439-89-6]; MA bove the Content elements", as disc	firmed that aluminum biller 12% post-consumer composition for alloying 7439-95-4]; Max 1.8% Max 0.5% Chromium [7440 Max 0.5% Chromium [7440 Inventory Threshold closed in the substance
SUBSTANCE NOTES: Solid extr used for this product consist of materials. In addition to the bas elements that may individually of Silicon [7440-21-3]; Max 1.5% N 47-3]; Max 0.05% Lead [7439-9 STAINLESS STEEL HARDWARE PRODUCT THRESHOLD: 100 ppm RESIDUALS AND IMPURITIES NOT indicated that have a GS score of Enotes.	f approximately 64% scrap aluminum, incluse metal, Aluminum [7429-90-5], documenta exceed the declared threshold: Max 2.5% 2 Manganese [7439-96-5]; Max 1.3% Copper 12-1]. %: 1.0000 - 5.0000 RESIDUALS AND IMPURITIES TES: No residuals or impurities are expected BM-1, LT-1, LT-P1 or NoGS other than those	mponents of the ladder uding 52% pre-consume ation from supplier prov Zinc [7440-66-6]; Max 2 · [7440-50-8]; Max 1.1%	MA Supplier has con- r press scrap and rides the following 1% Magnesium [ Iron [7439-89-6]; MA bove the Content elements", as disc	firmed that aluminum biller 12% post-consumer composition for alloying 7439-95-4]; Max 1.8% Max 0.5% Chromium [7440 Max 0.5% Chromium [7440 Inventory Threshold closed in the substance

UNS S30300 STAINLESS STEEL	ID: 12597-68-1			
HAZARD SCREENING METHOD:	Pharos Chemical and Materials Library	HAZARD SCI	REENING DATE:	2022-06-02 17:42:24
%: 100.0000 - 100.0000	GS: NoGS	RC: UNK	NANO: No	SUBSTANCE ROLE: Hardware
HAZARD TYPE	AGENCY AND LIST TITLES	WARN	INGS	
None found			No warnings f	ound on HPD Priority Hazard Lists

SUBSTANCE NOTES: Stainless steel screws, nuts and washers used to connect the ladder parts together. In addition to the base metal, Iron [7439-89-6], the standard composition for Type 303 Stainless Steel includes the following alloying elements that may individually exceed the declared threshold: 17-19% Chromium [7440-47-3]; 8-10% Nickel [7440-02-0]; Max 2.0% Manganese [7439-96-5]; Max 1.0% Silicon [7440-21-3].

This section lists applicable certification and standards compliance information for VOC emissions and VOC content. Other types of health or environmental performance testing or certifications completed for the product may be provided.

VOC EMISSIONS	Inherently non-emitting source per LEED®		
CERTIFYING PARTY: Self-declared APPLICABLE FACILITIES: Merced, CA 95341	ISSUE DATE: 2022-05- EXPIRY DATE: 24	CERTIFIER OR LAB: N/A	
CERTIFICATE URL:			

CERTIFICATION AND COMPLIANCE NOTES: Product is an inherently non-emitting source of VOCs (plated or anodized metal) as per LEED®.

# 😑 Section 4: Accessories

This section lists related products or materials that the manufacturer requires or recommends for installation (such as adhesives or fasteners), maintenance, cleaning, or operations. For information relating to the contents of these related products, refer to their applicable Health Product Declarations, if available.

No accessories are required for this product.

# Section 5: General Notes

#### MANUFACTURER INFORMATION

MANUFACTURER: SAFTI FIRST ADDRESS: 100 N Hill Drive Suite 12 Brisbane CA 94005, USA WEBSITE: https://safti.com/

CONTACT NAME: Diana San Diego TITLE: VP of Marketing PHONE: 888-653-3333 EMAIL: DianaS@safti.com

LT-1 List Translator 1 (Likely Benchmark-1)

to a LT-1 or LTP1 score.)

NoGS No GreenScreen.

LT-UNK List Translator Benchmark Unknown (the chemical is

information contained within the list did not result in a clear mapping

present on at least one GreenScreen Specified List, but the

The listed contact is responsible for the validity of this HPD and attests that it is accurate and complete to the best of his or her knowledge.

#### KEY

Hazard Types AQU Aquatic toxicity CAN Cancer DEV Developmental toxicity END Endocrine activity EYE Eye irritation/corrosivity

GEN Gene mutation GLO Global warming

### LAN Land toxicity MAM Mammalian/systemic/organ toxicity MUL Multiple NEU Neurotoxicity NF Not found on Priority Hazard Lists OZO Ozone depletion PBT Persistent, bioaccumulative, and toxic

PHY Physical hazard (flammable or reactive) REP Reproductive RES Respiratory sensitization SKI Skin sensitization/irritation/corrosivity UNK Unknown

#### GreenScreen (GS)

BM-4 Benchmark 4 (prefer-safer chemical)
BM-3 Benchmark 3 (use but still opportunity for improvement)
BM-2 Benchmark 2 (use but search for safer substitutes)
BM-1 Benchmark 1 (avoid - chemical of high concern)
BM-U Benchmark Unspecified (due to insufficient data)
LT-P1 List Translator Possible 1 (Possible Benchmark-1)

#### **Recycled Types**

PreC Pre-consumer recycled content PostC Post-consumer recycled content UNK Inclusion of recycled content is unknown None Does not include recycled content

#### Other Terms:

GHS SDS Globally Harmonized System of Classification and Labeling of Chemicals Safety Data Sheet

#### **Inventory Methods:**

Nested Method / Material Threshold Substances listed within each material per threshold indicated per material Nested Method / Product Threshold Substances listed within each material per threshold indicated per product Basic Method / Product Threshold Substances listed individually per threshold indicated per product

Nano Composed of nano scale particles or nanotechnology Third Party Verified Verification by independent certifier approved by HPDC Preparer Third party preparer, if not self-prepared by manufacturer Applicable facilities Manufacturing sites to which testing applies

The Health Product Declaration (HPD) Open Standard provides for the disclosure of product contents and potential associated human and environmental health hazards. Hazard associations are based on the HPD Priority Hazard Lists, the GreenScreen List Translator™, and when available, full GreenScreen® assessments. The HPD Open Standard v2.1 is not:

- a method for the assessment of exposure or risk associated with product handling or use,
- a method for assessing potential health impacts of: (i) substances used or created during the manufacturing process or (ii) substances created after the product is delivered for end use.

Information about life cycle, exposure and/or risk assessments performed on the product may be reported by the manufacturer in appropriate Notes sections, and/or, where applicable, in the Certifications section.

The HPD Open Standard was created and is supported by the Health Product Declaration Collaborative (the HPD Collaborative), a customer-led organization composed of stakeholders throughout the building industry that is committed to the continuous improvement of building products through transparency, openness, and innovation throughout the product supply chain.

The product manufacturer and any applicable independent verifier are solely responsible for the accuracy of statements and claims made in this HPD and for compliance with the HPD standard noted.